TECHNICAL DATA SHEET



Article code 158xxxxxx22s Article code 158xxxxxx23s

TK SCUFF FREE MATT (Bopp)

Profile: *Biaxially oriented polypropylene acrylic coated outside thermal laminating film

Features: *Good tear resistance

*Very good scuff resistant matt surface

*Acrylic coated matt surface is suitable for printing, hot foil stamping and UV spot varnish (initial test required)

*Glue-able, Bondable tests made on folder gluing machine with different water based glues brought good results

*See attached Declaration of compliance Page 2/2 for regulation information such as the REACH, SVHC & European toy standard EN 71-3.

Regulations & Directives:

* Acrylic coated matt surface is in accordance with article 16 of the EU Regulation 1935/2004

* Statement of composition only for secondary food packaging, the film is not suitable for direct contact with foodstuffs.

* The film is classified as articles according to the REACH regulation and therefore safety material data sheets are not necessary, because the substances contained in the film do not contain concentrations of 0.1% or more from the SVHC list.

Applications:

* Thermal lamination with all kinds of printed & unprinted paper, paperboards, book covers, posters,

magazines, diaries etc.

| Typical Properties +-5% | Unit | Test Method | Values |
|------------------------------------|-------------|-------------|-----------|
| Thickness | Microns | Internal | 29 |
| Unit Weight | g/m² | ASTM D792 | 25,7 |
| Yield | M²/kg | ASTM D792 | 39,0 |
| Gloss 60° (Matt Outside) | % | Internal | 5,0 |
| Surface tension glue side (inside) | Dynes/cm | Internal | 40 |
| Recommended laminating | °C | Internal | 100 ~ 115 |
| Coefficient of friction | Film / film | Internal | 0,35 |

<u>Recommended storage conditions</u>: For best performance store in a dry, clean location away from direct sunlight approx. between $20 \sim 30^{\circ}$ C, 40% relative humidity).

Disclaimer: The information provided above is to the best of knowledge of the supplier, the values provided are test results, which are indicative only and provided for guidelines.

Ultralen® registered trademark

The aforementioned data are given most conscientiously but without any obligation. Any processing details are provided merely for guidance, it is the user's responsibility to check the suitability of the product for the intended application.

<u>Warrantee</u>: This product has a warrantee of 180 days from the date on the invoice; claims after 180 days from the date on the invoice cannot be accepted. Please always keep the full label details of the roll available for warrantee purposes, without full label details claims cannot be accepted or handled normally.

Page 1/2

| USt.ID Nr.: | DE229822516 |
|------------------------|--|
| Steuer-Nr.: | 11089/06347 |
| Sitz der Gesellschaft: | Weil am Rhein |
| Registergericht: | Amtsgericht Freiburg HRB 413444 |
| Geschäftsführer: | Davide Froldi, Cristiano Conti, Giuliano Porta |

Ultralen Film GmbH Lustgartenstrasse 6 DE-79576 Weil am Rhein E-Mail: info@ultralen.com Internet: www.ultralen.com

TECHNICAL DATA SHEET



Article code 158xxxxxx22s Article code 158xxxxxx23s

TK SCUFF FREE MATT (Bopp)

Declaration of Compliance

Dear customer, we have confirmation from the film producer, and can confirm that the raw material components used in the TK Scuff free matt meets the requirements of the European Inventory of Existing Chemical (EINECS), the "EuPIA Exclusion Policy for Printing Inks and Regulated Products" This film type is in compliance with the REACH Regulation (EC) N°. 1907/2006.

Substances of very high concern

According to the technical knowledge of the Producer, this film does not contain any SVHC substances with a concentration of > 0.1 %. In addition, this film type does not contain any substances subject to authorization in Annex XIV and no restricted substances in Annex XVII of REACH Regulation (EC) N°1907/2006.

European toy standard EN 71-3: 2013

The European toy standard EN 71-3:2013 limits the content of certain elements such as aluminum, antimony, arsenic, barium, lead, boron, cadmium, chromium, cobalt, copper, manganese, nickel, organotin, mercury, selenium, strontium, zinc and tin into toys. We have confirmation that the limit values of the heavy metals mentioned above are not exceeded in this film type.

Furthermore, we have confirmation and can therefore confirm that this film type does not contain any of the following substances according to the knowledge of the producer of this film type.

-Silicone oils
-MOH (Mineral oil Hydrocarbons)
-MOSH (Mineral oil saturated Hydrocarbons)
-MOAH (Mineral oil aromatic Hydrocarbons)
-POSH (Polyolefin Oligomeric saturated Hydrocarbons)
-Oxo-Fragmental plastics

However, ubiquitous traces, which could occur everywhere, cannot be completely excluded.

This information is given to the best of the producer's knowledge.

Kind Regards: Ultralen Quality Management

Page 2/2

January 2023